

T14



Also available in
Cold Store Version -30°C



Speed Selector
to operate with the tiller
in the upright position

**The little helper
for a big earning of time**



High Frequency batteries charger built-in
with charge battery indicator and
block of the Forks with Flat battery

Pegasolift 

CE

T14 SERIES

DIMENSIONS SCHEME		GENERAL SPECIFICATIONS		
		MODEL	T14	
		Load capacity (Q)	1400 kg	
		Weight without load and with lead batteries	237 kg	
		Front rollers truck	460	
		Rear balance wheel truck	545	
		Front rollers size	poliurethane	n° 2 rollers ø 70 × 70
		Drive wheel size	poliurethane	ø 245×76
		Balance wheels size	poliurethane	ø 100 × 40
		Travel speed	with load	4,2 km/h
			without load	5,1 km/h
		Lifting speed	with load	0,072 m/s
			without load	0,110 m/s
		Lowering speed	with load	0,380 m/s
			without load	0,110 m/s
		Max Gradeability	with load	5,0%
without load	10,0%			
Brake	Electromagnetic			
Electronic control type	Mosfet 24V 110A			
Traction motor power	permanent magnets	700W		
Pump power motor	800W			
Battery charger built-in	High Frequency 24V 10A			
Noise	65 dB			
BATTERIES AVAILABLE				
n° 2 traction acid batteries 12V - 105Ah/20h		53 kg		
n° 2 traction GEL batteries 12V - 100Ah/20h		58 kg		

The high-efficiency and compact help



T14 addresses the need to handle material in extra small spaces. Its compact measurements allows maneuvering in a simple and agile way, even to non-professional users, saving time and money.

www.pegasolift.com

Pegasolift

Via del Lavoro 14 - 37047 San Bonifacio (Verona - Italy)
Tel. (0039) 045/7665570 - Fax: (0039) 045/7665698
www.pegasolift.com



All the pallet trucks of T14 series are manufactured according to the EEC Directive 98/37/CE