

# T14



Also available in  
Cold Store Version -30°C



Speed Selector  
to operate with the tiller  
in the upright position

**The little helper  
for a big earning of time**



High Frequency batteries charger built-in  
with charge battery indicator and  
block of the Forks with Flat battery

**Pegasolift** 

CE

# T14 SERIES

DIMENSIONS SCHEME		GENERAL SPECIFICATIONS		
<p>1 RUNNING 2 BRAKING</p> <p>Q=1400 kg</p> <p>LAST UPDATE: 14/09/2011</p>		MODEL	T14	
		Load capacity (Q)	1400 kg	
		Weight without load and with lead batteries	237 kg	
		Front rollers truck	460	
		Rear balance wheel truck	545	
		Front rollers size	poliurethane	n° 2 rollers ø 70 × 70
		Drive wheel size	poliurethane	ø 245×76
		Balance wheels size	poliurethane	ø 100 × 40
		Travel speed	with load	4,2 km/h
			without load	5,1 km/h
		Lifting speed	with load	0,072 m/s
			without load	0,110 m/s
		Lowering speed	with load	0,380 m/s
			without load	0,110 m/s
		Max Gradeability	with load	5,0%
	without load	10,0%		
Brake	Electromagnetic			
Electronic control type	Mosfet 24V 110A			
Traction motor power	permanent magnets	700W		
Pump power motor	800W			
Battery charger built-in	High Frequency 24V 10A			
Noise	65 dB			
<b>BATTERIES AVAILABLE</b>				
n° 2 traction acid batteries 12V - 105Ah/20h		53 kg		
n° 2 traction GEL batteries 12V - 100Ah/20h		58 kg		

## The high-efficiency and compact help



T14 addresses the need to handle material in extra small spaces. Its compact measurements allows maneuvering in a simple and agile way, even to non-professional users, saving time and money.

[www.pegasolift.com](http://www.pegasolift.com)

**Pegasolift**

Via del Lavoro 14 - 37047 San Bonifacio (Verona - Italy)  
Tel. (0039) 045/7665570 - Fax: (0039) 045/7665698  
[www.pegasolift.com](http://www.pegasolift.com)



All the pallet trucks of T14 series are manufactured according to the EEC Directive 98/37/CE