

TPL16 TPL20 TPL30



Fast/slow gear selector



Cold store version -30°C

Range of fork widths and lengths



COMPACT AND HANDY



Easy fork entry/exit rollers



Pegasolift 

CE

TPL Series

DIMENSIONS SCHEME				GENERAL SPECIFICATIONS																																																																																																																												
				<table border="1"> <tr> <td>MODEL</td> <td></td> <td>TPL16</td> <td>TPL20</td> <td>TPL30</td> </tr> <tr> <td>Load capacity (Q)</td> <td></td> <td>1600 kg</td> <td>2000 kg</td> <td>3000 kg</td> </tr> <tr> <td>Weight (without battery)</td> <td></td> <td>255 kg</td> <td>280 kg</td> <td>300 kg</td> </tr> <tr> <td>Front track</td> <td></td> <td colspan="3">485 / 585</td> </tr> <tr> <td>Rear track</td> <td></td> <td colspan="3">554</td> </tr> <tr> <td>Height of tiller in gear position (Brake releasing)</td> <td>min</td> <td colspan="3">790</td> </tr> <tr> <td></td> <td>max</td> <td colspan="3">1080</td> </tr> <tr> <td>Single front rollers size</td> <td>standard - poliurethane</td> <td>n° 2 rollers ø 85 × 90</td> <td colspan="2">N.D.</td> </tr> <tr> <td>Double front rollers size</td> <td>optional - poliurethane</td> <td colspan="3">n° 2+2 rollers ø 80 × 70 ⁽¹⁾</td> </tr> <tr> <td>Drive wheel size</td> <td>poliurethane</td> <td>ø 220×70</td> <td>ø 250×79</td> <td>ø 250×79</td> </tr> <tr> <td>Additional wheel size</td> <td>poliurethane</td> <td colspan="3">ø 100 × 40</td> </tr> <tr> <td rowspan="2">Travel speed</td> <td>with load</td> <td>4,8 km/h</td> <td>5,0 km/h</td> <td>4,8 km/h</td> </tr> <tr> <td>without load</td> <td>5,5 km/h</td> <td>6,0 km/h</td> <td>5,5 km/h</td> </tr> <tr> <td rowspan="2">Lifting speed</td> <td>with load</td> <td>0,014 m/s</td> <td>0,014 m/s</td> <td>0,014 m/s</td> </tr> <tr> <td>without load</td> <td>0,023 m/s</td> <td>0,023 m/s</td> <td>0,023 m/s</td> </tr> <tr> <td rowspan="2">Lowering speed</td> <td>with load</td> <td>0,045 m/s</td> <td>0,045 m/s</td> <td>0,045 m/s</td> </tr> <tr> <td>without load</td> <td>0,044 m/s</td> <td>0,044 m/s</td> <td>0,044 m/s</td> </tr> <tr> <td rowspan="2">Max gradeability</td> <td>with load</td> <td>6,0%</td> <td>7,0%</td> <td>7,0%</td> </tr> <tr> <td>without load</td> <td>17,0%</td> <td>17,5%</td> <td>17,5%</td> </tr> <tr> <td>Brake</td> <td></td> <td colspan="3">Elettromagnetic</td> </tr> <tr> <td>Electronic control type</td> <td></td> <td colspan="3">Mosfet 24V 200A</td> </tr> <tr> <td>Traction motor power</td> <td>Series Excite System</td> <td>800 W</td> <td>1200 W</td> <td>1200 W</td> </tr> <tr> <td>Pump power motor</td> <td></td> <td colspan="3">800W</td> </tr> <tr> <td>Noise</td> <td></td> <td colspan="3">65 dB</td> </tr> <tr> <td>Battery box size (L × W × H)</td> <td></td> <td colspan="3">215 × 635 × 660</td> </tr> </table>				MODEL		TPL16	TPL20	TPL30	Load capacity (Q)		1600 kg	2000 kg	3000 kg	Weight (without battery)		255 kg	280 kg	300 kg	Front track		485 / 585			Rear track		554			Height of tiller in gear position (Brake releasing)	min	790				max	1080			Single front rollers size	standard - poliurethane	n° 2 rollers ø 85 × 90	N.D.		Double front rollers size	optional - poliurethane	n° 2+2 rollers ø 80 × 70 ⁽¹⁾			Drive wheel size	poliurethane	ø 220×70	ø 250×79	ø 250×79	Additional wheel size	poliurethane	ø 100 × 40			Travel speed	with load	4,8 km/h	5,0 km/h	4,8 km/h	without load	5,5 km/h	6,0 km/h	5,5 km/h	Lifting speed	with load	0,014 m/s	0,014 m/s	0,014 m/s	without load	0,023 m/s	0,023 m/s	0,023 m/s	Lowering speed	with load	0,045 m/s	0,045 m/s	0,045 m/s	without load	0,044 m/s	0,044 m/s	0,044 m/s	Max gradeability	with load	6,0%	7,0%	7,0%	without load	17,0%	17,5%	17,5%	Brake		Elettromagnetic			Electronic control type		Mosfet 24V 200A			Traction motor power	Series Excite System	800 W	1200 W	1200 W	Pump power motor		800W			Noise		65 dB			Battery box size (L × W × H)		215 × 635 × 660		
MODEL		TPL16	TPL20	TPL30																																																																																																																												
Load capacity (Q)		1600 kg	2000 kg	3000 kg																																																																																																																												
Weight (without battery)		255 kg	280 kg	300 kg																																																																																																																												
Front track		485 / 585																																																																																																																														
Rear track		554																																																																																																																														
Height of tiller in gear position (Brake releasing)	min	790																																																																																																																														
	max	1080																																																																																																																														
Single front rollers size	standard - poliurethane	n° 2 rollers ø 85 × 90	N.D.																																																																																																																													
Double front rollers size	optional - poliurethane	n° 2+2 rollers ø 80 × 70 ⁽¹⁾																																																																																																																														
Drive wheel size	poliurethane	ø 220×70	ø 250×79	ø 250×79																																																																																																																												
Additional wheel size	poliurethane	ø 100 × 40																																																																																																																														
Travel speed	with load	4,8 km/h	5,0 km/h	4,8 km/h																																																																																																																												
	without load	5,5 km/h	6,0 km/h	5,5 km/h																																																																																																																												
Lifting speed	with load	0,014 m/s	0,014 m/s	0,014 m/s																																																																																																																												
	without load	0,023 m/s	0,023 m/s	0,023 m/s																																																																																																																												
Lowering speed	with load	0,045 m/s	0,045 m/s	0,045 m/s																																																																																																																												
	without load	0,044 m/s	0,044 m/s	0,044 m/s																																																																																																																												
Max gradeability	with load	6,0%	7,0%	7,0%																																																																																																																												
	without load	17,0%	17,5%	17,5%																																																																																																																												
Brake		Elettromagnetic																																																																																																																														
Electronic control type		Mosfet 24V 200A																																																																																																																														
Traction motor power	Series Excite System	800 W	1200 W	1200 W																																																																																																																												
Pump power motor		800W																																																																																																																														
Noise		65 dB																																																																																																																														
Battery box size (L × W × H)		215 × 635 × 660																																																																																																																														
<p>NOTE: the width of the forks of 660 mm is an optional</p>				<table border="1"> <thead> <tr> <th colspan="2"></th> <th colspan="4">BATTERY AVAILABLE</th> </tr> </thead> <tbody> <tr> <td>MODEL</td> <td></td> <td>TPL16</td> <td>TPL20</td> <td>TPL30</td> <td></td> </tr> <tr> <td>Length without forks</td> <td>D01</td> <td>570</td> <td>570</td> <td>570</td> <td>Traction battery 24V - 130Ah/5h</td> </tr> <tr> <td>Rear distance between axles</td> <td>D02</td> <td>167</td> <td>167</td> <td>167</td> <td>Traction battery 24V - 160Ah/5h</td> </tr> <tr> <td>Total length</td> <td>D03</td> <td>1720</td> <td>1720</td> <td>1720</td> <td>Traction battery 24V - 180Ah/5h</td> </tr> <tr> <td>Working isle width</td> <td>Ast</td> <td>1970</td> <td>1970</td> <td>1970</td> <td>Traction battery 24V - 230Ah/5h</td> </tr> <tr> <td>Steering radius</td> <td>R</td> <td>1531</td> <td>1531</td> <td>1531</td> <td></td> </tr> </tbody> </table>						BATTERY AVAILABLE				MODEL		TPL16	TPL20	TPL30		Length without forks	D01	570	570	570	Traction battery 24V - 130Ah/5h	Rear distance between axles	D02	167	167	167	Traction battery 24V - 160Ah/5h	Total length	D03	1720	1720	1720	Traction battery 24V - 180Ah/5h	Working isle width	Ast	1970	1970	1970	Traction battery 24V - 230Ah/5h	Steering radius	R	1531	1531	1531																																																																																
		BATTERY AVAILABLE																																																																																																																														
MODEL		TPL16	TPL20	TPL30																																																																																																																												
Length without forks	D01	570	570	570	Traction battery 24V - 130Ah/5h																																																																																																																											
Rear distance between axles	D02	167	167	167	Traction battery 24V - 160Ah/5h																																																																																																																											
Total length	D03	1720	1720	1720	Traction battery 24V - 180Ah/5h																																																																																																																											
Working isle width	Ast	1970	1970	1970	Traction battery 24V - 230Ah/5h																																																																																																																											
Steering radius	R	1531	1531	1531																																																																																																																												



PegasoLift

Via del Lavoro 14 - 37047 San Bonifacio (Verona - Italy)
Tel. (0039) 045/7665570 - Fax: (0039) 045/7665698
www.pegasolift.com

TPL is a pallet truck agile and sturdy, designed for the work in limited environment where permits an excellent manoeuvrability also at full load, thank to the powerful motor and to the reduced dimensions.

The switch to operate with the tiller in the upright position, placed on the control head, make much more simple avoid sudden accelerations during the delicate manoeuvres, avoiding useless damage to the goods and to the pallet truck.

The invitation rollers permit the lateral forking of the pallet reducing the working time and the manoeuvres needed.

All the series in equippable with various optional as: battery charge indicator with LCD hours counter and block of the forks with flat battery, trail-proof rubber wheel, lateral door for quick battery change and cold store version -30°C.

(1): TPL30 series are always equipped with the double front rollers; TPL30 are not available with the single front rollers.